

Package: gtexr (via r-universe)

September 23, 2024

Title Query the GTEx Portal API

Version 0.1.0.9000

Description A convenient R interface to the Genotype-Tissue Expression (GTEx) Portal API. For more information on the API, see <https://gtexportal.org/api/v2/redoc>.

License MIT + file LICENSE

URL <https://rmgpanw.github.io/gtexr/>, <https://github.com/rmgpanw/gtexr>

BugReports <https://github.com/rmgpanw/gtexr/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Imports cli, dplyr, httr2 (>= 1.0.0), purrr, rlang, tibble, tidyr

Suggests curl, httptest2, knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

Repository <https://rmgpanw.r-universe.dev>

RemoteUrl <https://github.com/rmgpanw/gtexr>

RemoteRef HEAD

RemoteSha 44fdac59118e94209bc7ce3735e57941a1ef087a

Contents

calculate_expression_quantitative_trait_loci	3
calculate_ieqtls	5
calculate_isqtls	6
calculate_splicing_quantitative_trait_loci	7
download	8
get_annotation	10
get_clustered_median_exon_expression	11
get_clustered_median_gene_expression	12

get_clustered_median_junction_expression	14
get_clustered_median_transcript_expression	15
get_collapsed_gene_model_exon	17
get_dataset_info	18
get_downloads_page_data	19
get_eqtl_genes	20
get_exons	21
get_expression_pca	22
get_file_list	24
get_fine_mapping	25
get_full_get_collapsed_gene_model_exon	26
get_functional_annotation	27
get_genes	28
get_gene_expression	29
get_gene_search	31
get_genomic_features	32
get_gwas_catalog_by_location	33
get_image	34
get_independent_eqtl	34
get_linkage_disequilibrium_by_variant_data	36
get_linkage_disequilibrium_data	37
get_maintenance_message	38
get_median_exon_expression	39
get_median_gene_expression	40
get_median_junction_expression	41
get_median_transcript_expression	42
get_multi_tissue_eqtls	43
get_neighbor_gene	45
get_news_item	46
get_sample_biobank_data	46
get_sample_datasets_endpoints	48
get_service_info	51
get_significant_single_tissue_eqtls	51
get_significant_single_tissue_eqtls_by_location	53
get_significant_single_tissue_ieqtls	54
get_significant_single_tissue_isqtls	55
get_significant_single_tissue_sqtls	57
get_single_nucleus_gex	58
get_single_nucleus_gex_summary	59
get_sqtls_genes	60
get_subject	62
get_tissue_site_detail	63
get_top_expressed_genes	64
get_transcripts	65
get_variant	66
get_variant_by_location	67

`calculate_expression_quantitative_trait_loci`*Calculate Expression Quantitative Trait Loci*

Description

Calculate your own eQTLs

- This service calculates the gene-variant association for any given pair of gene and variant, which may or may not be significant.
- This requires as input a GENCODE ID, GTEx variant ID, and tissue site detail ID.

By default, the calculation is based on the latest GTEx release.

[GTEx Portal API documentation](#).

Usage

```
calculate_expression_quantitative_trait_loci(  
  tissueSiteDetailId,  
  gencodeId,  
  variantId,  
  datasetId = "gtex_v8"  
)
```

Arguments

tissueSiteDetailId	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
gencodeId	String. A Versioned GENCODE ID of a gene, e.g. "ENSG00000065613.9".
variantId	String. A gtex variant ID.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

Details

Notes on output:

- Beta and standard error are recorded in columns `nes` and `error` respectively (see [GTEx FAQs](#))
- `variantId` contains (in order) chromosome, position, reference allele, alternative allele and human genome build separated by underscores. The reference and alternative alleles for "chr1_13550_G_A_b38" for example are "G" and "A" respectively.
- See examples for how to calculate minor and alternative allele frequencies.

Notes on input:

- Argument `variantId` also accepts RSIDs.

Value

A tibble.

See Also

Other Dynamic Association Endpoints: [calculate_ieqtls\(\)](#), [calculate_isqtls\(\)](#), [calculate_splicing_quantitative_trait_loci\(\)](#)

Examples

```
## Not run:
# perform request - returns a tibble with a single row
calculate_expression_quantitative_trait_loci(tissueSiteDetailId = "Whole_Blood",
                                             gencodeId = "ENSG00000203782.5",
                                             variantId = "rs79641866")

# unnest list columns with tidyr::unnest()
calculate_expression_quantitative_trait_loci(tissueSiteDetailId = "Whole_Blood",
                                             gencodeId = "ENSG00000203782.5",
                                             variantId = "rs79641866") |>
  tidyr::unnest(c("data", "genotypes"))

# to calculate minor and alternative allele frequencies
calculate_expression_quantitative_trait_loci(
  tissueSiteDetailId = "Liver",
  gencodeId = "ENSG00000237973.1",
  variantId = "rs12119111"
) |>
dplyr::bind_rows(.id = "rsid") |>

tidyr::separate(
  col = "variantId",
  into = c(
    "chromosome",
    "position",
    "reference_allele",
    "alternative_allele",
    "genome_build"
  ),
  sep = "_"
) |>

# ...then ascertain alternative_allele frequency
dplyr::mutate(
  alt_allele_count = (2 * homoAltCount) + hetCount,
  total_allele_count = 2 * (homoAltCount + hetCount + homoRefCount),
  alternative_allele_frequency = alt_allele_count / total_allele_count
) |>

dplyr::select(
  rsid,
  beta = nes,
  se = error,
```

```

    pValue,
    minor_allele_frequency = maf,
    alternative_allele_frequency,
    chromosome:genome_build,
    tissueSiteDetailId
)

## End(Not run)

```

calculate_ieqtls	<i>Calculate Ieqtls</i>
------------------	-------------------------

Description

Calculate your own Cell Specific eQTLs.

- This service calculates the gene-variant association for any given pair of gene and variant, which may or may not be significant.
- This requires as input a GENCODE ID, GTEx variant ID, and tissue site detail ID.

By default, the calculation is based on the latest GTEx release.

[GTEx Portal API documentation.](#)

Usage

```

calculate_ieqtls(
  cellType,
  tissueSiteDetailId,
  gencodeId,
  variantId,
  datasetId = "gtex_v8"
)

```

Arguments

cellType	String. "Adipocytes", "Epithelial_cells", "Hepatocytes", "Keratinocytes", "Myocytes", "Neurons", "Neutrophils".
tissueSiteDetailId	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
gencodeId	String. A Versioned GENCODE ID of a gene, e.g. "ENSG00000065613.9".
variantId	String. A gtex variant ID.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

Value

A tibble.

See Also

Other Dynamic Association Endpoints: [calculate_expression_quantitative_trait_loci\(\)](#), [calculate_isqtls\(\)](#), [calculate_splicing_quantitative_trait_loci\(\)](#)

Examples

```
## Not run:  
# perform request  
calculate_ieqtls(cellType = "Adipocytes",  
                tissueSiteDetailId = "Adipose_Subcutaneous",  
                gencodeId = "ENSG00000203782.5",  
                variantId = "chr1_1099341_T_C_b38")  
  
## End(Not run)
```

calculate_isqtls	<i>Calculate Isqtls</i>
------------------	-------------------------

Description

Calculate your own Cell Specific sQTLs.

- This service calculates the gene-variant association for any given pair of gene and variant, which may or may not be significant.
- This requires as input a GENCODE ID, GTEx variant ID, and tissue site detail ID.

By default, the calculation is based on the latest GTEx release.

[GTEx Portal API documentation.](#)

Usage

```
calculate_isqtls(  
  cellType,  
  tissueSiteDetailId,  
  phenotypeId,  
  variantId,  
  datasetId = "gtex_v8"  
)
```

Arguments

cellType	String. "Adipocytes", "Epithelial_cells", "Hepatocytes", "Keratinocytes", "Myocytes", "Neurons", "Neutrophils".
tissueSiteDetailId	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
phenotypeId	String. See GTEx portal FAQs for further details.
variantId	String. A gtex variant ID.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

Value

A tibble.

See Also

Other Dynamic Association Endpoints: [calculate_expression_quantitative_trait_loci\(\)](#), [calculate_ieqtls\(\)](#), [calculate_splicing_quantitative_trait_loci\(\)](#)

Examples

```
## Not run:
# perform request
calculate_isqtls(cellType = "Neutrophils",
                 tissueSiteDetailId = "Whole_Blood",
                 phenotypeId = "chr1:15947:16607:clu_40980:ENSG00000227232.5",
                 variantId = "chr1_1099341_T_C_b38")

## End(Not run)
```

```
calculate_splicing_quantitative_trait_loci
```

Calculate Splicing Quantitative Trait Loci

Description

[GTEx Portal API documentation.](#)

Usage

```
calculate_splicing_quantitative_trait_loci(
  tissueSiteDetailId,
  phenotypeId,
  variantId,
  datasetId = "gtex_v8"
)
```

Arguments

tissueSiteDetailId	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
phenotypeId	String. See GTEx portal FAQs for further details.
variantId	String. A gtex variant ID.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

Value

A tibble.

See Also

Other Dynamic Association Endpoints: [calculate_expression_quantitative_trait_loci\(\)](#), [calculate_ieqtls\(\)](#), [calculate_isqtls\(\)](#)

Examples

```
## Not run:
# perform request - returns a tibble with a single row
calculate_splicing_quantitative_trait_loci(
  tissueSiteDetailId = "Whole_Blood",
  phenotypeId = "chr1:15947:16607:clu_40980:ENSG00000227232.5",
  variantId = "chr1_14677_G_A_b38")

## End(Not run)
```

download

Download

Description

[GTEx Portal API documentation](#)

Usage

```
download(
  materialTypes = NULL,
  tissueSiteDetailIds = NULL,
  pathCategory = NULL,
  tissueSampleIds = NULL,
  sex = NULL,
  sortBy = NULL,
  sortDirection = NULL,
```



```

searchTerm = NULL,
sampleIds = NULL,
subjectIds = NULL,
ageBrackets = NULL,
hardyScales = NULL,
hasExpressionData = NULL,
hasGenotype = NULL
)

```

Arguments

materialTypes	String, vector. Options: "Cells:Cell Line Viable", "DNA:DNA Genomic", "DNA:DNA Somatic", "RNA:Total RNA", "Tissue:PAXgene Preserved", "Tissue:PAXgene Preserved Paraffin-embedded", "Tissue:Fresh Frozen Tissue".
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.
pathCategory	Character vector. Options: "adenoma", "amylacea", "atelectasis", "atherosclerosis", "atherosis", "atrophy", "calcification", "cirrhosis", "clean_specimens", "congestion", "corpora_albicantia", "cyst", "desquamation", "diabetic", "dysplasia", "edema", "emphysema", "esophagitis", "fibrosis", "gastritis", "glomerulosclerosis", "goiter", "gynecomastoid", "hashimoto", "heart_failure_cells", "hemorrhage", "hepatitis", "hyalinization", "hypereosinophilia", "hyperplasia", "hypertrophy", "hypoxic", "infarction", "inflammation", "ischemic_changes", "macrophages", "mastopathy", "metaplasia", "monckeberg", "necrosis", "nephritis", "nephrosclerosis", "no_abnormalities", "nodularity", "pancreatitis", "pigment", "pneumonia", "post_menopausal", "prostatitis", "saponification", "scarring", "sclerotic", "solar_elastosis", "spermatogenesis", "steatosis", "sweat_glands", "tma".
tissueSampleIds	Array of strings. A list of Tissue Sample ID(s).
sex	String. Options: "male", "female".
sortBy	String. Options: "sampleId", "ischemicTime", "aliquotId", "tissueSampleId", "hardyScale", "pathologyNotes", "ageBracket", "tissueSiteDetailId", "sex".
sortDirection	String. Options: "asc", "desc". Default = "asc".
searchTerm	String.
sampleIds	Character vector. GTEx sample ID.
subjectIds	Character vector. GTEx subject ID.
ageBrackets	The age bracket(s) of the donors of interest. Options: "20-29", "30-39", "40-49", "50-59", "60-69", "70-79".
hardyScales	Character vector. A list of Hardy Scale(s) of interest. Options: "Ventilator case", "Fast death - violent", "Fast death - natural causes", "Intermediate death", "Slow death".
hasExpressionData	Logical.
hasGenotype	Logical.

Details

Note: running this request with no filters (i.e. `download()`) raises an error.

Value

A tibble

See Also

Other Biobank Data Endpoints: [get_sample_biobank_data\(\)](#)

Examples

```
## Not run:
download(
  materialTypes = "RNA:Total RNA",
  tissueSiteDetailIds = "Thyroid",
  pathCategory = "clean_specimens",
  sex = "male",
  ageBrackets = "50-59"
)

## End(Not run)
```

get_annotation

Get Annotation

Description

This service returns the list of annotations and allowed values by which a particular dataset can be subsetted. Results may be filtered by dataset.

[GTEx Portal API documentation](#)

Usage

```
get_annotation(datasetId = "gtex_v8", page = 0, itemsPerPage = 250)
```

Arguments

datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Details

Note: the output for this function appears to be incomplete currently.

Value

A tibble

See Also

Other Datasets Endpoints: [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:  
get_annotation()  
  
## End(Not run)
```

get_clustered_median_exon_expression
Get Clustered Median Exon Expression

Description

Find median transcript expression data along with hierarchical clusters.

- Returns median normalized transcript expression in tissues of all known transcripts of a given gene along with the hierarchical clustering results of tissues and transcripts, based on exon expression, in Newick format.
- The hierarchical clustering is performed by calculating Euclidean distances and using the average linkage method.
- **This endpoint is not paginated.**

By default, this endpoint queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_clustered_median_exon_expression(  
  gencodeIds,  
  datasetId = "gtex_v8",  
  tissueSiteDetailIds = NULL  
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.

Value

A tibble, with clustering data stored as an attribute, "clusters".

See Also

Other Expression Data Endpoints: `get_clustered_median_gene_expression()`, `get_clustered_median_junction_exp`, `get_clustered_median_transcript_expression()`, `get_expression_pca()`, `get_gene_expression()`, `get_median_exon_expression()`, `get_median_gene_expression()`, `get_median_junction_expression()`, `get_median_transcript_expression()`, `get_single_nucleus_gex()`, `get_single_nucleus_gex_summary()`, `get_top_expressed_genes()`

Examples

```
## Not run:
get_clustered_median_exon_expression(c("ENSG00000203782.5",
                                       "ENSG00000132693.12"))

# clustering data is stored as an attribute "clusters"
result <- get_clustered_median_exon_expression(c("ENSG00000203782.5",
                                                "ENSG00000132693.12"))

attr(result, "clusters")

# process clustering data with the ape package
# install.packages("ape")
# phylo_tree <- ape::read.tree(text = attr(result, "clusters")$tissue)
# plot(phylo_tree)
# print(phylo_tree)

## End(Not run)
```

`get_clustered_median_gene_expression`

Get Clustered Median Gene Expression

Description

Find median gene expression data along with hierarchical clusters.

- Returns median gene expression in tissues along with The hierarchical clustering results of tissues and genes, based on gene expression, in Newick format.
- Results may be filtered by dataset, gene or tissue, but at least one gene must be provided
- The hierarchical clustering is performed by calculating Euclidean distances and using the average linkage method.
- **This endpoint is not paginated.**

By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_clustered_median_gene_expression(  
  gencodeIds,  
  datasetId = "gtex_v8",  
  tissueSiteDetailIds = NULL  
)
```

Arguments

gencodeIds	A character vector of Versioned GENCODE IDs, e.g. c("ENSG00000132693.12", "ENSG00000203782.5").
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.

Value

A tibble, with clustering data stored as an attribute, "clusters".

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:
get_clustered_median_gene_expression(gencodeIds = c("ENSG00000203782.5",
                                                  "ENSG00000132693.12"))

# clustering data is stored as an attribute "clusters"
result <- get_clustered_median_gene_expression(c("ENSG00000203782.5",
                                               "ENSG00000132693.12"))

attr(result, "clusters")

# process clustering data with the ape package
# install.packages("ape")
# phylo_tree <- ape::read.tree(text = attr(result, "clusters")$tissue)
# plot(phylo_tree)
# print(phylo_tree)

## End(Not run)
```

```
get_clustered_median_junction_expression
      Get Clustered Median Junction Expression
```

Description

Find median junction expression data along with hierarchical clusters.

- Returns median junction read counts in tissues of a given gene from all known transcripts along with the hierarchical clustering results of tissues and genes, based on junction expression, in Newick format.
- Results may be filtered by dataset, gene or tissue, but at least one gene must be provided.
- The hierarchical clustering is performed by calculating Euclidean distances and using the average linkage method.
- **This endpoint is not paginated.**

By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_clustered_median_junction_expression(
  gencodeIds,
  datasetId = "gtex_v8",
  tissueSiteDetailIds = NULL
)
```

Arguments

gencodeIds	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.

Value

A tibble, with clustering data stored as an attribute, "clusters".

See Also

Other Expression Data Endpoints: `get_clustered_median_exon_expression()`, `get_clustered_median_gene_expression()`, `get_clustered_median_transcript_expression()`, `get_expression_pca()`, `get_gene_expression()`, `get_median_exon_expression()`, `get_median_gene_expression()`, `get_median_junction_expression()`, `get_median_transcript_expression()`, `get_single_nucleus_gex()`, `get_single_nucleus_gex_summary()`, `get_top_expressed_genes()`

Examples

```
## Not run:
get_clustered_median_junction_expression(gencodeIds = c("ENSG00000203782.5",
                                                    "ENSG00000132693.12"))

# clustering data is stored as an attribute "clusters"
result <- get_clustered_median_junction_expression(c("ENSG00000203782.5",
                                                    "ENSG00000132693.12"))

attr(result, "clusters")

# process clustering data with the ape package
# install.packages("ape")
# phylo_tree <- ape::read.tree(text = attr(result, "clusters")$tissue)
# plot(phylo_tree)
# print(phylo_tree)

## End(Not run)
```

get_clustered_median_transcript_expression

Get Clustered Median Transcript Expression

Description

Find median transcript expression data of all known transcripts of a gene along with hierarchical clusters.

- Returns median normalized expression in tissues of all known transcripts of a given gene along with the hierarchical clustering results of tissues and genes, based on expression, in Newick format.
- Results may be filtered by dataset, gene or tissue, but at least one gene must be provided.
- The hierarchical clustering is performed by calculating Euclidean distances and using the average linkage method.
- **This endpoint is not paginated.**

By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_clustered_median_transcript_expression(
  gencodeIds,
  datasetId = "gtex_v8",
  tissueSiteDetailIds = NULL
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.

Value

A tibble, with clustering data stored as an attribute, "clusters".

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:
get_clustered_median_transcript_expression(gencodeIds = c("ENSG00000203782.5",
                                                         "ENSG00000132693.12"))

# clustering data is stored as an attribute "clusters"
result <- get_clustered_median_transcript_expression(c("ENSG00000203782.5",
                                                         "ENSG00000132693.12"))

attr(result, "clusters")

# process clustering data with the ape package
# install.packages("ape")
# phylo_tree <- ape::read.tree(text = attr(result, "clusters")$tissue)
# plot(phylo_tree)
# print(phylo_tree)

## End(Not run)
```

```
get_collapsed_gene_model_exon
```

Get Collapsed Gene Model Exon

Description

This service returns the collapsed exons in the gene model of the given gene. Gene-level and exon-level expression quantification were based on the GENCODE annotation, collapsed to a single transcript model for each gene using an algorithm developed by the GTEx analysis team.

By default, this service queries the models used by the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_collapsed_gene_model_exon(
  gencodeId,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

gencodeId	String. A Versioned GENCODE ID of a gene, e.g. "ENSG00000065613.9".
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_endpoints\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:
  get_collapsed_gene_model_exon(gencodeId = "ENSG00000132693.12")

## End(Not run)
```

get_dataset_info	<i>Get Dataset Info</i>
------------------	-------------------------

Description

[GTEx Portal API documentation](#)

Usage

```
get_dataset_info(datasetId = "gtex_v8", organizationName = "GTEx Consortium")
```

Arguments

datasetId String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

organizationName String. Options: "GTEx Consortium" "Kid's First".

Details

Note: this current only returns empty values.

Value

A tibble.

Examples

```
## Not run:
  get_dataset_info()

## End(Not run)
```

`get_downloads_page_data`*Get Downloads Page Data*

Description

Retrieves all the files belonging to the given `project_id` for display on the Downloads Page

[GTEx Portal API documentation](#)

Usage

```
get_downloads_page_data(project_id = "adult-gtex")
```

Arguments

`project_id` String. Options: "gtex", "adult-gtex", "egtex".

Details

Note: The GTEx Portal API documentation states "GTEx currently has one project available: gtex". However, `project_id` values "adult-gtex" and "egtex" both return results, whereas "gtex" does not (see examples).

Value

A Tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_endpoints\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:
# "adult-gtex" (default `project_id` value) and "egtex" both return results
get_downloads_page_data()
egtex <- get_downloads_page_data("egtex")
egtex

# ..."gtex" does not
get_downloads_page_data("gtex")

# get details for whole blood methylation data, including download URL
purrr::pluck(
  egtex$children,
```

```

1,
"folders",
"Methylation - EPIC Array",
"children",
"folders",
"mQTLs",
"children",
"files",
"WholeBlood.mQTLs.regular.txt.gz"
)

## End(Not run)

```

get_eqtl_genes

Get Eqtl Genes

Description

Retrieve eGenes (eQTL Genes).

- This service returns eGenes (eQTL Genes) from the specified dataset.
- eGenes are genes that have at least one significant cis-eQTL acting upon them.
- Results may be filtered by tissue. By default, the service queries the latest GTEx release.

For each eGene, the results include the allelic fold change (`log2AllelicFoldChange`), p-value (`pValue`), p-value threshold (`pValueThreshold`), empirical p-value (`empiricalPValue`), and q-value (`qValue`).

- The `log2AllelicFoldChange` is the allelic fold change (in log₂ scale) of the most significant eQTL.
- The `pValue` is the nominal p-value of the most significant eQTL.
- The `pValueThreshold` is the p-value threshold used to determine whether a cis-eQTL for this gene is significant. For more details see <https://gtexportal.org/home/documentationPage#staticTextAnalysisMethods>.
- The `empiricalPValue` is the beta distribution-adjusted empirical p-value from FastQTL.
- The `qValues` were calculated based on the empirical p-values. A false discovery rate (FDR) threshold of ≤ 0.05 was applied to identify genes with a significant eQTL.

[GTEx Portal API documentation.](#)

Usage

```

get_eqtl_genes(
  tissueSiteDetailIds,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)

```

Arguments

tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Static Association Endpoints: [get_fine_mapping\(\)](#), [get_independent_eqtl\(\)](#), [get_multi_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls_by_location\(\)](#), [get_significant_single_tissue_ieqtls\(\)](#), [get_significant_single_tissue_isqtls\(\)](#), [get_significant_single_tissue_isqtls_by_location\(\)](#), [get_sqt1_genes\(\)](#)

Examples

```
## Not run:
get_eqtl_genes(c("Whole_Blood", "Artery_Aorta"))

## End(Not run)
```

get_exons

Get Exons

Description

This service returns exons from all known transcripts of the given gene.

- A versioned GENCODE ID is required to ensure that all exons are from a single gene.
- A dataset ID or both GENCODE version and genome build must be provided.
- Although annotated exons are not dataset dependent, specifying a dataset here is equivalent to specifying the GENCODE version and genome build used by that dataset.

[GTEx Portal API documentation](#)

Usage

```
get_exons(
  gencodeId,
  gencodeVersion = NULL,
  genomeBuild = NULL,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

gencodeId	String. A Versioned GENCODE ID of a gene, e.g. "ENSG00000065613.9".
gencodeVersion	String (default = "v26"). GENCODE annotation release. Either "v26" or "v19".
genomeBuild	String. Options: "GRCh38/hg38", "GRCh37/hg19". Default = "GRCh38/hg38".
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Reference Genome Endpoints: [get_gene_search\(\)](#), [get_genes\(\)](#), [get_genomic_features\(\)](#), [get_gwas_catalog_by_location\(\)](#), [get_neighbor_gene\(\)](#), [get_transcripts\(\)](#)

Examples

```
## Not run:
get_exons(gencodeId = "ENSG00000203782.5")

## End(Not run)
```

get_expression_pca *Get Expression Pca*

Description

Find gene expression PCA data.

- Returns gene expression PCA (principal component analysis) in tissues.
- Results may be filtered by tissue, sample, or dataset.

By default, the service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_expression_pca(
  tissueSiteDetailIds,
  datasetId = "gtex_v8",
  sampleId = NULL,
  page = 0,
  itemsPerPage = 250
)
```

Arguments

tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
sampleId	String. <code>^GTEx-[A-Z0-9]{5}-[0-9]{4}-SM-[A-Z0-9]{5}\$</code>
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:
get_expression_pca(tissueSiteDetailIds = c("Adipose_Subcutaneous",
                                           "Whole_Blood"))

get_expression_pca(tissueSiteDetailIds = "Adipose_Subcutaneous",
                  sampleId = "GTEx-1117F-0226-SM-5GZZ7")

## End(Not run)
```

`get_file_list`*Get File List*

Description

Get all the files in GTEx dataset for Download page

[GTEx Portal API documentation](#)

Usage

```
get_file_list()
```

Details

The returned tibble includes a nested list column, "filesets". This details files, sub-categorised by fileset (see examples section).

Value

A tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_v](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_endpoints\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:
# Column "filesets" is a list column
get_file_list()

# Get "GTEx Analysis V9" file list
gtex_v9_files <- get_file_list() |>
  dplyr::filter(name == "GTEx Analysis V9") |>
  dplyr::pull(filesets)

# "GTEx Analysis V9" filesets
names(gtex_v9_files[[1]])

# "GTEx Analysis V9", "snRNA-Seq Data" fileset files
names(gtex_v9_files[[1]][["snRNA-Seq Data"]]$files)

## End(Not run)
```

get_fine_mapping	<i>Get Fine Mapping</i>
------------------	-------------------------

Description

Retrieve Fine Mapping Data

- Finds and returns Fine Mapping data for the provided list of genes
- By default, this endpoint fetches data from the latest GTEx version

The retrieved data is split into pages with `items_per_page` entries per page

[GTEx Portal API documentation](#)

Usage

```
get_fine_mapping(
  gencodeIds,
  datasetId = "gtex_v8",
  variantId = NULL,
  tissueSiteDetailIds = NULL,
  page = 0,
  itemsPerPage = 250
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: <code>"gtex_v8"</code> , <code>"gtex_snrnaseq_pilot"</code> .
<code>variantId</code>	String. A gtex variant ID.
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. <code>"Whole_Blood"</code> ; use get_tissue_site_detail() to see valid values) or Ontology IDs.
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble.

See Also

Other Static Association Endpoints: [get_eqtl_genes\(\)](#), [get_independent_eqtl\(\)](#), [get_multi_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls_by_location\(\)](#), [get_significant_single_tissue_ieqtls\(\)](#), [get_significant_single_tissue_isqtls\(\)](#), [get_significant_single_eqtl_genes\(\)](#)

Examples

```
## Not run:
# search by gene
get_fine_mapping(gencodeIds = c("ENSG00000132693.12",
                                "ENSG00000203782.5"))

# optionally filter for a single variant and/or one or more tissues
get_fine_mapping(gencodeIds = c("ENSG00000132693.12",
                                "ENSG00000203782.5"),
                variantId = "chr1_153228363_A_G_b38",
                tissueSiteDetailIds = c("Whole_Blood",
                                        "Thyroid"))

## End(Not run)
```

```
get_full_get_collapsed_gene_model_exon
Get Full Get Collapsed Gene Model Exon
```

Description

This service allows the user to query the full Collapsed Gene Model Exon of a specific gene by gencode ID

[GTEx Portal API documentation](#)

Usage

```
get_full_get_collapsed_gene_model_exon(gencodeId, page = 0, itemsPerPage = 250)
```

Arguments

gencodeId	String. A Versioned GENCODE ID of a gene, e.g. "ENSG00000065613.9".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_endpoints\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:  
  get_full_get_collapsed_gene_model_exon(gencodeId = "ENSG00000203782.5")  
  
## End(Not run)
```

```
get_functional_annotation  
  Get Functional Annotation
```

Description

This endpoint retrieves the functional annotation of a certain chromosome location. Default to most recent dataset release.

[GTEx Portal API documentation](#)

Usage

```
get_functional_annotation(  
  datasetId = "gtex_v8",  
  chromosome,  
  start,  
  end,  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
chromosome	String. One of "chr1", "chr2", "chr3", "chr4", "chr5", "chr6", "chr7", "chr8", "chr9", "chr10", "chr11", "chr12", "chr13", "chr14", "chr15", "chr16", "chr17", "chr18", "chr19", "chr20", "chr21", "chr22", "chrM", "chrX", "chrY".
start	Integer.
end	Integer.
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_endpoints\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:
  get_functional_annotation(chromosome = "chr1", start = 192168000, end = 192169000)

## End(Not run)
```

 get_genes

Get Genes

Description

This service returns information about reference genes. A genome build and GENCODE version must be provided.

- Genes are searchable by gene symbol, GENCODE ID and versioned GENCODE ID.
- Versioned GENCODE ID is recommended to ensure unique ID matching.
- By default, this service queries the genome build and GENCODE version used by the latest GTEx release.

[GTEx API Portal documentation](#)

Usage

```
get_genes(
  geneIds,
  gencodeVersion = "v26",
  genomeBuild = "GRCh38/hg38",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

geneIds	A character vector of gene symbols, versioned gencodeIds, or unversioned gencodeIds.
gencodeVersion	String (default = "v26"). GENCODE annotation release. Either "v26" or "v19".
genomeBuild	String. Options: "GRCh38/hg38", "GRCh37/hg19". Default = "GRCh38/hg38".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Reference Genome Endpoints: [get_exons\(\)](#), [get_gene_search\(\)](#), [get_genomic_features\(\)](#), [get_gwas_catalog_by_location\(\)](#), [get_neighbor_gene\(\)](#), [get_transcripts\(\)](#)

Examples

```
## Not run:  
get_genes(c("CRP", "IL6R"))  
  
## End(Not run)
```

get_gene_expression *Get Gene Expression*

Description

Find normalized gene expression data.

- Returns normalized gene expression in tissues at the sample level.
- Results may be filtered by dataset, gene or tissue, but at least one gene must be provided.

By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_gene_expression(  
  gencodeIds,  
  datasetId = "gtex_v8",  
  tissueSiteDetailIds = NULL,  
  attributeSubset = NULL,  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

gencodeIds	A character vector of Versioned GENCODE IDs, e.g. c("ENSG00000132693.12", "ENSG00000203782.5").
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.
attributeSubset	String. Examples include but are not limited to "sex", "ageBracket"
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: `get_clustered_median_exon_expression()`, `get_clustered_median_gene_expression()`, `get_clustered_median_junction_expression()`, `get_clustered_median_transcript_expression()`, `get_expression_pca()`, `get_median_exon_expression()`, `get_median_gene_expression()`, `get_median_junction_expression()`, `get_median_transcript_expression()`, `get_single_nucleus_gex()`, `get_single_nucleus_gex_summary()`, `get_top_expressed_genes()`

Examples

```
## Not run:
# multiple genes, selected tissues
get_gene_expression(gencodeIds = c("ENSG00000132693.12",
                                  "ENSG00000203782.5"),
                   tissueSiteDetailIds = c("Thyroid", "Whole_Blood"))

# single gene, selected (single) tissue
get_gene_expression(gencodeIds = "ENSG00000132693.12",
                   tissueSiteDetailIds = "Whole_Blood")

# subset by sex
get_gene_expression(gencodeIds = "ENSG00000132693.12",
                   tissueSiteDetailIds = "Whole_Blood",
                   attributeSubset = "sex")

# subset by age bracket
get_gene_expression(gencodeIds = "ENSG00000132693.12",
                   tissueSiteDetailIds = "Whole_Blood",
                   attributeSubset = "ageBracket")

## End(Not run)
```

get_gene_search	<i>Get Gene Search</i>
-----------------	------------------------

Description

Find genes that are partial or complete match of a gene_id

- gene_id could be a gene symbol, a gencode ID, or an Ensemble ID
- Gencode Version and Genome Build must be specified

[GTEx Portal API documentation](#)

Usage

```
get_gene_search(  
  geneId,  
  gencodeVersion = "v26",  
  genomeBuild = "GRCh38/hg38",  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

geneId	String. A gene symbol, a gencode ID, or an Ensemble ID.
gencodeVersion	String (default = "v26"). GENCODE annotation release. Either "v26" or "v19".
genomeBuild	String. Options: "GRCh38/hg38", "GRCh37/hg19". Default = "GRCh38/hg38".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Reference Genome Endpoints: [get_exons\(\)](#), [get_genes\(\)](#), [get_genomic_features\(\)](#), [get_gwas_catalog_by_location\(\)](#), [get_neighbor_gene\(\)](#), [get_transcripts\(\)](#)

Examples

```
## Not run:  
get_gene_search("CRP")  
  
## End(Not run)
```

get_genomic_features *Get Genomic Features*

Description

[GTEx API Portal documentation](#)

Usage

```
get_genomic_features(.featureId, datasetId = "gtex_v8")
```

Arguments

.featureId	String. A genomic feature e.g. GENCODE ID, RSID or GTEx Variant ID.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

Details

This endpoint takes a path parameter "featureId".

Value

A tibble.

See Also

Other Reference Genome Endpoints: [get_exons\(\)](#), [get_gene_search\(\)](#), [get_genes\(\)](#), [get_gwas_catalog_by_location\(\)](#), [get_neighbor_gene\(\)](#), [get_transcripts\(\)](#)

Examples

```
## Not run:  
# gene symbol  
get_genomic_features("brca1")  
  
# GENCODE ID  
get_genomic_features("ENSG00000132693.12")  
  
# RSID  
get_genomic_features("rs1815739")  
  
# GTEx variant ID  
get_genomic_features("chr11_66561023_G_GTTA_b38")  
  
## End(Not run)
```

get_gwas_catalog_by_location
Get Gwas Catalog By Location

Description

Find the GWAS Catalog on a certain chromosome between start and end locations.

[GTEx API Portal documentation](#)

Usage

```
get_gwas_catalog_by_location(  
  start,  
  end,  
  chromosome,  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

start	Integer.
end	Integer.
chromosome	String. One of "chr1", "chr2", "chr3", "chr4", "chr5", "chr6", "chr7", "chr8", "chr9", "chr10", "chr11", "chr12", "chr13", "chr14", "chr15", "chr16", "chr17", "chr18", "chr19", "chr20", "chr21", "chr22", "chrM", "chrX", "chrY".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Reference Genome Endpoints: [get_exons\(\)](#), [get_gene_search\(\)](#), [get_genes\(\)](#), [get_genomic_features\(\)](#), [get_neighbor_gene\(\)](#), [get_transcripts\(\)](#)

Examples

```
## Not run:  
get_gwas_catalog_by_location(start = 1, end = 10000000, chromosome = "chr1")  
  
## End(Not run)
```

get_image *Get Image*

Description

[GTEX Portal API documentation](#)

Usage

```
get_image(tissueSampleIds = NULL, page = 0, itemsPerPage = 250)
```

Arguments

tissueSampleIds	Array of strings. A list of Tissue Sample ID(s).
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

Examples

```
## Not run:
get_image()

# filter by `tissueSampleId`
result <- get_image(tissueSampleIds = "GTEX-1117F-0526")
print(result)

# note that `pathologyNotesCategories` (if present) is a list column
print(result$pathologyNotesCategories)

## End(Not run)
```

get_independent_eqtl *Get Independent Eqtl*

Description

Retrieve Independent eQTL Data

- Finds and returns Independent eQTL Data data for the provided list of genes
- By default, this endpoint fetches data from the latest GTEX version

The retrieved data is split into pages with `items_per_page` entries per page

[GTEX portal API documentation](#)

`get_linkage_disequilibrium_by_variant_data`*Get Linkage Disequilibrium By Variant Data*

Description

Find linkage disequilibrium (LD) data for a given variant

[GTEx Portal API documentation](#)

Usage

```
get_linkage_disequilibrium_by_variant_data(  
  variantId,  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

<code>variantId</code>	String. A gtex variant ID.
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble.

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_endpoints\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
get_linkage_disequilibrium_by_variant_data("chr1_159245536_C_T_b38")
```

get_linkage_disequilibrium_data
Get Linkage Disequilibrium Data

Description

Find linkage disequilibrium (LD) data for a given gene.

This endpoint returns linkage disequilibrium data for the cis-eQTLs found associated with the provided gene in a specified dataset. Results are queried by gencode ID. By default, the service queries the latest GTEx release. Specify a dataset ID to fetch results from a different dataset.

[GTEx Portal API documentation](#)

Usage

```
get_linkage_disequilibrium_data(  
  gencodeId,  
  datasetId = "gtex_v8",  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

gencodeId	String. A Versioned GENCODE ID of a gene, e.g. "ENSG00000065613.9".
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_sample_datasets_endpoints\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
get_linkage_disequilibrium_data(gencodeId = "ENSG00000132693.12")
```

`get_maintenance_message`*Get Maintenance Message*

Description

Getting all the maintenance messages from the database that are enabled.

[GTEx Portal API documentation](#).

Usage

```
get_maintenance_message(page = 0, itemsPerPage = 250)
```

Arguments

<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Details

Note this typically returns an empty tibble.

Value

A tibble.

See Also

Other Admin Endpoints: [get_news_item\(\)](#)

Examples

```
## Not run:  
get_maintenance_message()  
  
## End(Not run)
```

`get_median_exon_expression`*Get Median Exon Expression*

Description

Find median exon expression data.

- Returns median exon read counts, in tissues, of a collapsed gene model.
- Results may be filtered by dataset, gene or tissue, but at least one gene must be provided

By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_median_exon_expression(  
  gencodeIds,  
  datasetId = "gtex_v8",  
  tissueSiteDetailIds = NULL,  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:
# median exon expression values for CRP, filtered for whole blood
get_median_exon_expression(gencodeIds = "ENSG00000132693.12",
                           tissueSiteDetailIds = "Whole_Blood")

## End(Not run)
```

```
get_median_gene_expression
      Get Median Gene Expression
```

Description

Find median gene expression data along with hierarchical clusters.

- Returns median gene expression in tissues.
- By default, this endpoint queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_median_gene_expression(
  gencodeIds,
  datasetId = "gtex_v8",
  tissueSiteDetailIds = NULL,
  page = 0,
  itemsPerPage = 250
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:
get_median_gene_expression(gencodeIds = "ENSG00000132693.12")

## End(Not run)
```

```
get_median_junction_expression
      Get Median Junction Expression
```

Description

Find junction gene expression data.

- Returns median junction read counts in tissues of a given gene from all known transcripts.
- Results may be filtered by dataset or tissue.

By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_median_junction_expression(
  gencodeIds,
  datasetId = "gtex_v8",
  tissueSiteDetailIds = NULL,
  page = 0,
  itemsPerPage = 250
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: <code>"gtex_v8"</code> , <code>"gtex_snrnaseq_pilot"</code> .
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. <code>"Whole_Blood"</code> ; use get_tissue_site_detail() to see valid values) or Ontology IDs.

page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:  
get_median_junction_expression(gencodeIds = "ENSG00000132693.12")  
  
## End(Not run)
```

get_median_transcript_expression
Get Median Transcript Expression

Description

Find median transcript expression data of all known transcripts of a gene.

- Returns median normalized expression in tissues of all known transcripts of a given gene.
- Results may be filtered by dataset or tissue.

By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_median_transcript_expression(  
  gencodeIds,  
  datasetId = "gtex_v8",  
  tissueSiteDetailIds = NULL,  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

gencodeIds	A character vector of Versioned GENCODE IDs, e.g. c("ENSG00000132693.12", "ENSG00000203782.5").
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:
get_median_transcript_expression(gencodeIds = "ENSG00000132693.12")

## End(Not run)
```

```
get_multi_tissue_eqtls
```

Get Multi Tissue Eqtls

Description

Find multi-tissue eQTL Metasoft results.

- This service returns multi-tissue eQTL Metasoft results for a given gene and variant in a specified dataset.
- A Versioned GENCODE ID must be provided.
- For each tissue, the results include: m-value (mValue), normalized effect size (nes), p-value (pValue), and standard error (se).
- The m-value is the posterior probability that an eQTL effect exists in each tissue tested in the cross-tissue meta-analysis (Han and Eskin, PLoS Genetics 8(3): e1002555, 2012).

- The normalized effect size is the slope of the linear regression of normalized expression data versus the three genotype categories using single-tissue eQTL analysis, representing eQTL effect size.
- The p-value is from a t-test that compares observed NES from single-tissue eQTL analysis to a null NES of 0.

By default, the service queries the latest GTEx release. The retrieved data is split into pages with `items_per_page` entries per page

[GTEx Portal API documentation](#)

Usage

```
get_multi_tissue_eqtls(
  gencodeIds,
  variantId = NULL,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>variantId</code>	String. A gtex variant ID.
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble.

See Also

Other Static Association Endpoints: [get_eqtl_genes\(\)](#), [get_fine_mapping\(\)](#), [get_independent_eqtl\(\)](#), [get_significant_single_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls_by_location\(\)](#), [get_significant_single_tissue_ieqtls\(\)](#), [get_significant_single_tissue_isqtls\(\)](#), [get_significant_single_tissue_sqtl_genes\(\)](#)

Examples

```
## Not run:
# search by gene
get_multi_tissue_eqtls(gencodeId = c("ENSG00000132693.12",
                                     "ENSG00000203782.5"))

## End(Not run)
```

get_neighbor_gene	<i>Get Neighbor Gene</i>
-------------------	--------------------------

Description

Find all neighboring genes on a certain chromosome around a position with a certain window size.

[GTEx API Portal documentation](#)

Usage

```
get_neighbor_gene(pos, chromosome, bp_window, page = 0, itemsPerPage = 250)
```

Arguments

pos	Integer, vector.
chromosome	String. One of "chr1", "chr2", "chr3", "chr4", "chr5", "chr6", "chr7", "chr8", "chr9", "chr10", "chr11", "chr12", "chr13", "chr14", "chr15", "chr16", "chr17", "chr18", "chr19", "chr20", "chr21", "chr22", "chrM", "chrX", "chrY".
bp_window	Integer.
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Reference Genome Endpoints: [get_exons\(\)](#), [get_gene_search\(\)](#), [get_genes\(\)](#), [get_genomic_features\(\)](#), [get_gwas_catalog_by_location\(\)](#), [get_transcripts\(\)](#)

Examples

```
## Not run:  
get_neighbor_gene(pos = 1000000, chromosome = "chr1", bp_window = 10000)  
  
## End(Not run)
```

get_news_item	<i>Get News Item</i>
---------------	----------------------

Description

Getting all the news items from the database that are current.

[GTEEx Portal API documentation.](#)

Usage

```
get_news_item(page = 0, itemsPerPage = 250)
```

Arguments

page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Admin Endpoints: [get_maintenance_message\(\)](#)

Examples

```
## Not run:  
get_news_item()  
  
## End(Not run)
```

get_sample_biobank_data	<i>Get Sample (Biobank Data)</i>
-------------------------	----------------------------------

Description

[GTEEx Portal API documentation](#)

Usage

```

get_sample_biobank_data(
  draw = NULL,
  materialTypes = NULL,
  tissueSiteDetailIds = NULL,
  pathCategory = NULL,
  tissueSampleIds = NULL,
  sex = NULL,
  sortBy = "sampleId",
  sortDirection = "asc",
  searchTerm = NULL,
  sampleIds = NULL,
  subjectIds = NULL,
  ageBrackets = NULL,
  hardyScales = NULL,
  hasExpressionData = NULL,
  hasGenotype = NULL,
  page = 0,
  itemsPerPage = 250
)

```

Arguments

draw	Integer.
materialTypes	String, vector. Options: "Cells:Cell Line Viable", "DNA:DNA Genomic", "DNA:DNA Somatic", "RNA:Total RNA", "Tissue:PAXgene Preserved", "Tissue:PAXgene Preserved Paraffin-embedded", "Tissue:Fresh Frozen Tissue".
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEX specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
pathCategory	Character vector. Options: "adenoma", "amylacea", "atelectasis", "atherosclerosis", "atherosis", "atrophy", "calcification", "cirrhosis", "clean_specimens", "congestion", "corpora_albicantia", "cyst", "desquamation", "diabetic", "dysplasia", "edema", "emphysema", "esophagitis", "fibrosis", "gastritis", "glomerulosclerosis", "goiter", "gynecomastoid", "hashimoto", "heart_failure_cells", "hemorrhage", "hepatitis", "hyalinization", "hypereosinophilia", "hyperplasia", "hypertrophy", "hypoxic", "infarction", "inflammation", "ischemic_changes", "macrophages", "mastopathy", "metaplasia", "monckeberg", "necrosis", "nephritis", "nephrosclerosis", "no_abnormalities", "nodularity", "pancreatitis", "pigment", "pneumonia", "post_menopausal", "prostatitis", "saponification", "scarring", "sclerotic", "solar_elastosis", "spermatogenesis", "steatosis", "sweat_glands", "tma".
tissueSampleIds	Array of strings. A list of Tissue Sample ID(s).
sex	String. Options: "male", "female".
sortBy	String. Options: "sampleId", "ischemicTime", "aliquotId", "tissueSampleId", "hardyScale", "pathologyNotes", "ageBracket", "tissueSiteDetailId", "sex".

sortDirection	String. Options: "asc", "desc". Default = "asc".
searchTerm	String.
sampleIds	Character vector. GTEEx sample ID.
subjectIds	Character vector. GTEEx subject ID.
ageBrackets	The age bracket(s) of the donors of interest. Options: "20-29", "30-39", "40-49", "50-59", "60-69", "70-79".
hardyScales	Character vector. A list of Hardy Scale(s) of interest. Options: "Ventilator case", "Fast death - violent", "Fast death - natural causes", "Intermediate death", "Slow death".
hasExpressionData	Logical.
hasGenotype	Logical.
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Biobank Data Endpoints: [download\(\)](#)

Examples

```
## Not run:  
get_sample_biobank_data(tissueSiteDetailIds = "Whole_Blood")  
  
## End(Not run)
```

get_sample_datasets_endpoints

Get Sample (Datasets Endpoints)

Description

This service returns information of samples used in analyses from all datasets. Results may be filtered by dataset ID, sample ID, subject ID, sample metadata, or other provided parameters. By default, this service queries the latest GTEEx release.

[GTEEx Portal API documentation](#)

Usage

```

get_sample_datasets_endpoints(
  datasetId = "gtex_v8",
  sampleIds = NULL,
  tissueSampleIds = NULL,
  subjectIds = NULL,
  ageBrackets = NULL,
  sex = NULL,
  pathCategory = NULL,
  tissueSiteDetailId = NULL,
  aliquotIds = NULL,
  autolysisScores = NULL,
  hardyScales = NULL,
  ischemicTime = NULL,
  ischemicTimeGroups = NULL,
  rin = NULL,
  uberonIds = NULL,
  dataTypes = NULL,
  sortBy = NULL,
  sortDirection = NULL,
  page = NULL,
  itemsPerPage = NULL
)

```

Arguments

datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
sampleIds	Character vector. GTEX sample ID.
tissueSampleIds	Array of strings. A list of Tissue Sample ID(s).
subjectIds	Character vector. GTEX subject ID.
ageBrackets	The age bracket(s) of the donors of interest. Options: "20-29", "30-39", "40-49", "50-59", "60-69", "70-79".
sex	String. Options: "male", "female".
pathCategory	Character vector. Options: "adenoma", "amylacea", "atelectasis", "atherosclerosis", "atherosis", "atrophy", "calcification", "cirrhosis", "clean_specimens", "congestion", "corpora_albicantia", "cyst", "desquamation", "diabetic", "dysplasia", "edema", "emphysema", "esophagitis", "fibrosis", "gastritis", "glomerulosclerosis", "goiter", "gynecomastoid", "hashimoto", "heart_failure_cells", "hemorrhage", "hepatitis", "hyalinization", "hypereosinophilia", "hyperplasia", "hypertrophy", "hypoxic", "infarction", "inflammation", "ischemic_changes", "macrophages", "mastopathy", "metaplasia", "monckeberg", "necrosis", "nephritis", "nephrosclerosis", "no_abnormalities", "nodularity", "pancreatitis", "pigment", "pneumonia", "post_menopausal", "prostatitis", "saponification", "scarring", "sclerotic", "solar_elastosis", "spermatogenesis", "steatosis", "sweat_glands", "tma".

tissueSiteDetailId	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
aliquotIds	Character vector.
autolysisScores	Character vector. Options: "None", "Mild", "Moderate", "Severe".
hardyScales	Character vector. A list of Hardy Scale(s) of interest. Options: "Ventilator case", "Fast death - violent", "Fast death - natural causes", "Intermediate death", "Slow death".
ischemicTime	Integer.
ischemicTimeGroups	Character vector. Options: "<= 0", "1 - 300", "301 - 600", "601 - 900", "901 - 1200", "1201 - 1500", "> 1500".
rin	Integer vector.
uberonIds	Character vector of Uberon IDs (e.g. "UBERON:EFO_0000572"; use get_tissue_site_detail() to see valid values).
dataTypes	Character vector. Options: "RNASEQ", "WGS", "WES", "OMNI", "EXCLUDE".
sortBy	String. Options: "sampleId", "ischemicTime", "aliquotId", "tissueSampleId", "hardyScale", "pathologyNotes", "ageBracket", "tissueSiteDetailId", "sex".
sortDirection	String. Options: "asc", "desc". Default = "asc".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:
  get_sample_datasets_endpoints()

## End(Not run)
```

get_service_info *Get Service Info*

Description

General information about the GTEx service.

[GTEx Portal API documentation.](#)

Usage

```
get_service_info()
```

Value

A tibble.

Examples

```
## Not run:  
get_service_info()  
  
## End(Not run)
```

get_significant_single_tissue_eqtls
Get Significant Single Tissue Eqtls

Description

Find significant single tissue eQTLs.

- This service returns precomputed significant single tissue eQTLs.
- Results may be filtered by tissue, gene, variant or dataset.
- To search by gene, use the versioned GENCODE ID.
- To search by variant, use the dbSNP rs ID (snpId).

By default, the service queries the latest GTEx release and the retrieved data is split into pages with `items_per_page` entries per page

[GTEx Portal API documentation.](#)

Usage

```
get_significant_single_tissue_eqtls(
  gencodeIds = NULL,
  variantIds = NULL,
  tissueSiteDetailIds = NULL,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

gencodeIds	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
variantIds	Character vector. Gtex variant IDs.
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEX specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Details

Note: although the GTEX Portal API documentation says to use the dbSNP rsID when searching by variant, this returns no results. Instead use gtex variant IDs e.g. use "chr1_153209640_C_A_b38" instead of "rs1410858".

Value

A tibble.

See Also

Other Static Association Endpoints: `get_eqtl_genes()`, `get_fine_mapping()`, `get_independent_eqtl()`, `get_multi_tissue_eqtls()`, `get_significant_single_tissue_eqtls_by_location()`, `get_significant_single_tissue_eqtls()`, `get_significant_single_tissue_isqtls()`, `get_significant_single_tissue_sqtls()`, `get_sqtls_genes()`

Examples

```
## Not run:
# search by gene
get_significant_single_tissue_eqtls(gencodeIds = c("ENSG00000132693.12",
                                                "ENSG00000203782.5"))

# search by variant - must be variantId (not rsid)
```

```

get_significant_single_tissue_eqtls(variantIds = "chr1_153209640_C_A_b38")

# filter by gene/variant and tissue site - either `gencodeIds` or `variantIds`
# should be supplied as a minimum
get_significant_single_tissue_eqtls(gencodeIds = c("ENSG00000132693.12",
                                                "ENSG00000203782.5"),
                                   variantIds = "chr1_153209640_C_A_b38",
                                   tissueSiteDetailIds = "Whole_Blood")

## End(Not run)

```

```

get_significant_single_tissue_eqtls_by_location
    Get Significant Single Tissue eQTLs By Location

```

Description

Find significant single tissue eQTLs using Chromosomal Locations.

- This service returns precomputed significant single tissue eQTLs.
- Results may be filtered by tissue, and/or dataset.

By default, the service queries the latest GTEx release. Since this endpoint is used to support a third party program on the portal, the return structure is different from other endpoints and is not paginated.

[GTEx Portal API documentation](#)

Usage

```

get_significant_single_tissue_eqtls_by_location(
  tissueSiteDetailId,
  start,
  end,
  chromosome,
  datasetId = "gtex_v8"
)

```

Arguments

tissueSiteDetailId	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
start	Integer.
end	Integer.
chromosome	String. One of "chr1", "chr2", "chr3", "chr4", "chr5", "chr6", "chr7", "chr8", "chr9", "chr10", "chr11", "chr12", "chr13", "chr14", "chr15", "chr16", "chr17", "chr18", "chr19", "chr20", "chr21", "chr22", "chrM", "chrX", "chrY".

datasetId String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

Value

A tibble.

See Also

Other Static Association Endpoints: [get_eqtl_genes\(\)](#), [get_fine_mapping\(\)](#), [get_independent_eqtl\(\)](#), [get_multi_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls\(\)](#), [get_significant_single_tissue_ieqtls\(\)](#), [get_significant_single_tissue_isqtls\(\)](#), [get_significant_single_tissue_sqtls\(\)](#), [get_sqtls_genes\(\)](#)

Examples

```
## Not run:
get_significant_single_tissue_eqtls_by_location(
  tissueSiteDetailId = "Artery_Aorta",
  start = 10000,
  end = 250000,
  chromosome = "chr11")

## End(Not run)
```

`get_significant_single_tissue_ieqtls`

Get Significant Single Tissue Ieqtls

Description

Retrieve Interaction eQTL Data.

- This service returns cell type interaction eQTLs (ieQTLs), from a specified dataset.
- Results may be filtered by tissue
- By default, the service queries the latest GTEx release.

The retrieved data is split into pages with `items_per_page` entries per page

[GTEx Portal API documentation](#)

Usage

```
get_significant_single_tissue_ieqtls(
  gencodeIds,
  variantIds = NULL,
  tissueSiteDetailIds = NULL,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

gencodeIds	A character vector of Versioned GENCODE IDs, e.g. c("ENSG00000132693.12", "ENSG00000203782.5").
variantIds	Character vector. Gtex variant IDs.
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Static Association Endpoints: [get_eqtl_genes\(\)](#), [get_fine_mapping\(\)](#), [get_independent_eqtl\(\)](#), [get_multi_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls\(\)](#), [get_significant_single_tissue_eqtls_L\(\)](#), [get_significant_single_tissue_isqtls\(\)](#), [get_significant_single_tissue_sqtls\(\)](#), [get_sqtl_genes\(\)](#)

Examples

```
## Not run:
get_significant_single_tissue_ieqtls(c("ENSG00000132693.12",
                                     "ENSG00000203782.5"))

## End(Not run)
```

get_significant_single_tissue_isqtls
et Significant Single Tissue Isqtls

Description

Retrieve Interaction sQTL Data.

- This service retrieves cell type interaction sQTLs (isQTLs), from a specified dataset.
- Results may be filtered by tissue
- By default, the service queries the latest GTEx release.

The retrieved data is split into pages with `items_per_page` entries per page

[GTEx Portal API documentation](#).

Usage

```
get_significant_single_tissue_isqtls(
  gencodeIds,
  variantIds = NULL,
  tissueSiteDetailIds = NULL,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>variantIds</code>	Character vector. Gtex variant IDs.
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble

See Also

Other Static Association Endpoints: `get_eqtl_genes()`, `get_fine_mapping()`, `get_independent_eqtl()`, `get_multi_tissue_eqtls()`, `get_significant_single_tissue_eqtls()`, `get_significant_single_tissue_eqtls_`, `get_significant_single_tissue_ieqtls()`, `get_significant_single_tissue_sqtls()`, `get_sqtls_genes()`

Examples

```
## Not run:
get_significant_single_tissue_isqtls(gencodeIds = c("ENSG00000065613.9",
                                                    "ENSG00000203782.5"))

## End(Not run)
```

get_significant_single_tissue_sqtls
Get Significant Single Tissue Sqtls

Description

Retrieve Single Tissue sQTL Data.

- This service returns single tissue sQTL data for the given genes, from a specified dataset.
- Results may be filtered by tissue
- By default, the service queries the latest GTEx release.

The retrieved data is split into pages with `items_per_page` entries per page

[GTEx Portal API documentation](#).

Usage

```
get_significant_single_tissue_sqtls(  
  gencodeIds,  
  variantIds = NULL,  
  tissueSiteDetailIds = NULL,  
  datasetId = "gtex_v8"  
)
```

Arguments

<code>gencodeIds</code>	A character vector of Versioned GENCODE IDs, e.g. <code>c("ENSG00000132693.12", "ENSG00000203782.5")</code> .
<code>variantIds</code>	Character vector. Gtex variant IDs.
<code>tissueSiteDetailIds</code>	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use <code>get_tissue_site_detail()</code> to see valid values) or Ontology IDs.
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".

Value

A tibble

See Also

Other Static Association Endpoints: `get_eqtl_genes()`, `get_fine_mapping()`, `get_independent_eqtl()`, `get_multi_tissue_eqtls()`, `get_significant_single_tissue_eqtls()`, `get_significant_single_tissue_eqtls_l`, `get_significant_single_tissue_ieqtls()`, `get_significant_single_tissue_isqtls()`, `get_sqtls_genes()`

Examples

```
## Not run:
# search by gene
get_significant_single_tissue_sqtl(gencodeIds = c("ENSG00000065613.9",
                                                "ENSG00000203782.5"))

## End(Not run)
```

```
get_single_nucleus_gex
```

```
Get Single Nucleus Gex
```

Description

Retrieve Single Nucleus Gene Expression Data for a given Gene.

[GTEx Portal API documentation](#)

Usage

```
get_single_nucleus_gex(
  gencodeIds,
  datasetId = "gtex_snrnaseq_pilot",
  tissueSiteDetailIds = NULL,
  excludeDataArray = TRUE,
  page = 0,
  itemsPerPage = 250
)
```

Arguments

gencodeIds	A character vector of Versioned GENCODE IDs, e.g. c("ENSG00000132693.12", "ENSG00000203782.5").
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
excludeDataArray	String. Options are TRUE or FALSE
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex_summary\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```
## Not run:
# Search for one or more genes - returns a tibble with one row per tissue.
# Column "cellTypes" now contains a tibble of expression summary data, with
# one row for each cell type
get_single_nucleus_gex(gencodeIds = c("ENSG00000203782.5",
                                     "ENSG00000132693.12"))

# `excludeDataArray = FALSE` - expression values are stored under "celltypes"
# in an additional column called "data"
response <- get_single_nucleus_gex(gencodeIds = "ENSG00000132693.12",
                                  excludeDataArray = FALSE,
                                  itemsPerPage = 2)

response

# "cellTypes" contains a tibble of data with one row for each
# cell type e.g. for Breast_Mammary_Tissue
response$cellTypes[[2]]

# when `excludeDataArray = FALSE`, expression values are stored in "data"
# e.g. for Breast_Mammary_Tissue, Epithelial cell (luminal):
response$cellTypes[[2]]$data[[1]]

## End(Not run)
```

```
get_single_nucleus_gex_summary
```

Get Single Nucleus Gex Summary

Description

Retrieve Summarized Single Nucleus Gene Expression Data.

[GTEx Portal API documentation](#)

Usage

```
get_single_nucleus_gex_summary(
  datasetId = "gtex_snrnaseq_pilot",
  tissueSiteDetailIds = NULL,
```

```

    page = 0,
    itemsPerPage = 250
  )

```

Arguments

datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
tissueSiteDetailIds	Character vector of IDs for tissues of interest. Can be GTEx specific IDs (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or Ontology IDs.
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_top_expressed_genes\(\)](#)

Examples

```

## Not run:
# all tissues
get_single_nucleus_gex_summary()

# filter for specific tissue
get_single_nucleus_gex_summary(tissueSiteDetailIds = c("Breast_Mammary_Tissue",
                                                    "Skin_Sun_Exposed_Lower_leg"))

## End(Not run)

```

Description

Retrieve sGenes (sQTL Genes).

- This service returns sGenes (sQTL Genes) from the specified dataset.
- Results may be filtered by tissue.
- By default, the service queries the latest GTEx release.

The retrieved data is split into pages with `items_per_page` entries per page

[GTEx Portal API documentation](#).

Usage

```
get_sqtL_genes(
  tissueSiteDetailId,
  datasetId = "gtex_v8",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

<code>tissueSiteDetailId</code>	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble.

See Also

Other Static Association Endpoints: [get_eqtL_genes\(\)](#), [get_fine_mapping\(\)](#), [get_independent_eqtL\(\)](#), [get_multi_tissue_eqtLs\(\)](#), [get_significant_single_tissue_eqtLs\(\)](#), [get_significant_single_tissue_eqtLs_L](#), [get_significant_single_tissue_ieqtLs\(\)](#), [get_significant_single_tissue_isqtLs\(\)](#), [get_significant_single](#)

Examples

```
## Not run:
get_sqtL_genes("Whole_Blood")

## End(Not run)
```

get_subject

Get Subject

Description

This service returns information of subjects used in analyses from all datasets. Results may be filtered by dataset ID, subject ID, sex, age bracket or Hardy Scale. By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_subject(
  datasetId = "gtex_v8",
  sex = NULL,
  ageBrackets = NULL,
  hardyScales = NULL,
  subjectIds = NULL,
  page = 0,
  itemsPerPage = 250
)
```

Arguments

datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
sex	String. Options: "male", "female".
ageBrackets	The age bracket(s) of the donors of interest. Options: "20-29", "30-39", "40-49", "50-59", "60-69", "70-79".
hardyScales	Character vector. A list of Hardy Scale(s) of interest. Options: "Ventilator case", "Fast death - violent", "Fast death - natural causes", "Intermediate death", "Slow death".
subjectIds	Character vector. GTEx subject ID.
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A Tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:  
  get_subject()  
  
## End(Not run)
```

get_tissue_site_detail

Get Tissue Site Detail

Description

Retrieve all tissue site detail information in the database

[GTEx Portal API documentation](#)

Usage

```
get_tissue_site_detail(page = 0, itemsPerPage = 250)
```

Arguments

page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets_](#), [get_subject\(\)](#), [get_variant\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
## Not run:  
# returns a tibble with one row per tissue  
get_tissue_site_detail()  
  
# `eqtlSampleSummary` and `rnaSeqSampleSummary` are list columns  
bladder_site_details <- get_tissue_site_detail() |>  
  dplyr::filter(tissueSiteDetailId == "Bladder")  
  
purrr::pluck(bladder_site_details, "eqtlSampleSummary", 1)  
  
purrr::pluck(bladder_site_details, "rnaSeqSampleSummary", 1)
```

```
## End(Not run)
```

```
get_top_expressed_genes
  Get Top Expressed Genes
```

Description

Find top expressed genes for a specified tissue.

- Returns top expressed genes for a specified tissue in a dataset, sorted by median expression.
- When the optional parameter `filterMtGene` is set to true, mitochondrial genes will be excluded from the results. By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_top_expressed_genes(
  tissueSiteDetailId,
  datasetId = "gtex_v8",
  filterMtGene = TRUE,
  page = 0,
  itemsPerPage = 250
)
```

Arguments

<code>tissueSiteDetailId</code>	String. The ID of the tissue of interest. Can be a GTEx specific ID (e.g. "Whole_Blood"; use get_tissue_site_detail() to see valid values) or an Ontology ID.
<code>datasetId</code>	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
<code>filterMtGene</code>	Logical. Exclude mitochondrial genes.
<code>page</code>	Integer (default = 0).
<code>itemsPerPage</code>	Integer (default = 250).

Value

A tibble.

See Also

Other Expression Data Endpoints: [get_clustered_median_exon_expression\(\)](#), [get_clustered_median_gene_expression\(\)](#), [get_clustered_median_junction_expression\(\)](#), [get_clustered_median_transcript_expression\(\)](#), [get_expression_pca\(\)](#), [get_gene_expression\(\)](#), [get_median_exon_expression\(\)](#), [get_median_gene_expression\(\)](#), [get_median_junction_expression\(\)](#), [get_median_transcript_expression\(\)](#), [get_single_nucleus_gex\(\)](#), [get_single_nucleus_gex_summary\(\)](#)

Examples

```
## Not run:
get_top_expressed_genes(tissueSiteDetailId = "Artery_Aorta")

## End(Not run)
```

get_transcripts	<i>Get Transcripts</i>
-----------------	------------------------

Description

Find all transcripts of a reference gene.

- This service returns information about transcripts of the given versioned GENCODE ID.
- A genome build and GENCODE version must be provided.
- By default, this service queries the genome build and GENCODE version used by the latest GTEx release.

[GTEx API Portal documentation](#)

Usage

```
get_transcripts(  
  gencodeId,  
  gencodeVersion = "v26",  
  genomeBuild = "GRCh38/hg38",  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

gencodeId	String. A Versioned GENCODE ID of a gene, e.g. "ENSG00000065613.9".
gencodeVersion	String (default = "v26"). GENCODE annotation release. Either "v26" or "v19".
genomeBuild	String. Options: "GRCh38/hg38", "GRCh37/hg19". Default = "GRCh38/hg38".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Reference Genome Endpoints: [get_exons\(\)](#), [get_gene_search\(\)](#), [get_genes\(\)](#), [get_genomic_features\(\)](#), [get_gwas_catalog_by_location\(\)](#), [get_neighbor_gene\(\)](#)

Examples

```
## Not run:  
get_transcripts(gencodeId = "ENSG00000203782.5")  
  
## End(Not run)
```

get_variant

Get Variant

Description

This service returns information about a variant, including position, dbSNP RS ID, the reference allele, the alternative allele, and whether the minor allele frequency is $\geq 1\%$. For GTEx v6p, there is also information about whether the whole exome sequence and chip sequencing data are available. Results may be queried by GTEx variant ID (variantId), dbSNP RS ID (snpId) or genomic location (chromosome and pos). Variants are identified based on the genotype data of each dataset cohort, namely, are dataset-dependent. Each variant is assigned a unique GTEx variant ID (i.e. the primary key). Not all variants have a mappable dbSNP RS ID. By default, this service queries the latest GTEx release.

[GTEx Portal API documentation](#)

Usage

```
get_variant(  
  snpId = NULL,  
  variantId = NULL,  
  chromosome = NULL,  
  pos = NULL,  
  datasetId = "gtex_v8",  
  page = 0,  
  itemsPerPage = 250  
)
```

Arguments

snpId	String
variantId	String. A gtex variant ID.
chromosome	String. One of "chr1", "chr2", "chr3", "chr4", "chr5", "chr6", "chr7", "chr8", "chr9", "chr10", "chr11", "chr12", "chr13", "chr14", "chr15", "chr16", "chr17", "chr18", "chr19", "chr20", "chr21", "chr22", "chrM", "chrX", "chrY".
pos	Integer, vector.
datasetId	String. Unique identifier of a dataset. Usually includes a data source and data release. Options: "gtex_v8", "gtex_snrnaseq_pilot".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant_by_location\(\)](#)

Examples

```
# search by rsid
get_variant(snpId = "rs1410858")

# search by variantId
get_variant(variantId = "chr1_153209640_C_A_b38")

# search by chromosome and position
get_variant(chromosome = "chr1",
            pos = 153209600:153209700)
```

get_variant_by_location

Get Variant By Location

Description

This service allows the user to query information about variants on a certain chromosome at a certain location.

[GTEx Portal API documentation](#)

Usage

```
get_variant_by_location(
  start,
  end,
  chromosome,
  sortBy = "pos",
  sortDirection = "asc",
  page = 0,
  itemsPerPage = 250
)
```

Arguments

start	Integer.
end	Integer.
chromosome	String. One of "chr1", "chr2", "chr3", "chr4", "chr5", "chr6", "chr7", "chr8", "chr9", "chr10", "chr11", "chr12", "chr13", "chr14", "chr15", "chr16", "chr17", "chr18", "chr19", "chr20", "chr21", "chr22", "chrM", "chrX", "chrY".
sortBy	String. Options: "sampleId", "ischemicTime", "aliquotId", "tissueSampleId", "hardyScale", "pathologyNotes", "ageBracket", "tissueSiteDetailId", "sex".
sortDirection	String. Options: "asc", "desc". Default = "asc".
page	Integer (default = 0).
itemsPerPage	Integer (default = 250).

Value

A tibble.

See Also

Other Datasets Endpoints: [get_annotation\(\)](#), [get_collapsed_gene_model_exon\(\)](#), [get_downloads_page_data\(\)](#), [get_file_list\(\)](#), [get_full_get_collapsed_gene_model_exon\(\)](#), [get_functional_annotation\(\)](#), [get_linkage_disequilibrium_by_variant_data\(\)](#), [get_linkage_disequilibrium_data\(\)](#), [get_sample_datasets\(\)](#), [get_subject\(\)](#), [get_tissue_site_detail\(\)](#), [get_variant\(\)](#)

Examples

```
get_variant_by_location(start = 153209600,
  end = 153209700,
  chromosome = "chr1")
```

Index

- * **Admin Endpoints**
 - get_maintenance_message, 38
 - get_news_item, 46
- * **Biobank Data Endpoints**
 - download, 8
 - get_sample_biobank_data, 46
- * **Datasets Endpoints**
 - get_annotation, 10
 - get_collapsed_gene_model_exon, 17
 - get_downloads_page_data, 19
 - get_file_list, 24
 - get_full_get_collapsed_gene_model_exon, 26
 - get_functional_annotation, 27
 - get_linkage_disequilibrium_by_variant_data, 36
 - get_linkage_disequilibrium_data, 37
 - get_sample_datasets_endpoints, 48
 - get_subject, 62
 - get_tissue_site_detail, 63
 - get_variant, 66
 - get_variant_by_location, 67
- * **Dynamic Association Endpoints**
 - calculate_expression_quantitative_trait_loci, 3
 - calculate_ieqtls, 5
 - calculate_isqtls, 6
 - calculate_splicing_quantitative_trait_loci, 7
- * **Expression Data Endpoints**
 - get_clustered_median_exon_expression, 11
 - get_clustered_median_gene_expression, 12
 - get_clustered_median_junction_expression, 14
 - get_clustered_median_transcript_expression, 15
 - get_expression_pca, 22
 - get_gene_expression, 29
 - get_median_exon_expression, 39
 - get_median_gene_expression, 40
 - get_median_junction_expression, 41
 - get_median_transcript_expression, 42
 - get_single_nucleus_gex, 58
 - get_single_nucleus_gex_summary, 59
 - get_top_expressed_genes, 64
- * **GTEX Portal API Info**
 - get_service_info, 51
- * **Histology Endpoints**
 - get_image, 34
- * **Metadata Endpoints**
 - get_dataset_info, 18
- * **Reference Genome Endpoints**
 - get_exons, 21
 - get_gene_search, 31
 - get_genes, 28
 - get_genomic_features, 32
 - get_gwas_catalog_by_location, 33
 - get_neighbor_gene, 45
 - get_transcripts, 65
- * **Static Association Endpoints**
 - get_eqtl_genes, 20
 - get_fine_mapping, 25
 - get_independent_eqtl, 34
 - get_multi_tissue_eqtls, 43
 - get_significant_single_tissue_eqtls, 51
 - get_significant_single_tissue_eqtls_by_location, 53
 - get_significant_single_tissue_ieqtls, 54
 - get_significant_single_tissue_isqtls, 55
 - get_significant_single_tissue_sqtls, 57

- get_sqtl_genes, 60
- calculate_expression_quantitative_trait_loci, 3, 6–8
- calculate_ieqtls, 4, 5, 7, 8
- calculate_isqtls, 4, 6, 6, 8
- calculate_splicing_quantitative_trait_loci, 4, 6, 7, 7
- download, 8, 48
- get_annotation, 10, 18, 19, 24, 26, 28, 36, 37, 50, 62, 63, 67, 68
- get_clustered_median_exon_expression, 11, 13, 15, 16, 23, 30, 39, 41–43, 59, 60, 65
- get_clustered_median_gene_expression, 12, 12, 15, 16, 23, 30, 39, 41–43, 59, 60, 65
- get_clustered_median_junction_expression, 12, 13, 14, 16, 23, 30, 39, 41–43, 59, 60, 65
- get_clustered_median_transcript_expression, 12, 13, 15, 15, 23, 30, 39, 41–43, 59, 60, 65
- get_collapsed_gene_model_exon, 11, 17, 19, 24, 26, 28, 36, 37, 50, 62, 63, 67, 68
- get_dataset_info, 18
- get_downloads_page_data, 11, 18, 19, 24, 26, 28, 36, 37, 50, 62, 63, 67, 68
- get_eqtl_genes, 20, 25, 35, 44, 52, 54–57, 61
- get_exons, 21, 29, 31–33, 45, 66
- get_expression_pca, 12, 13, 15, 16, 22, 30, 39, 41–43, 59, 60, 65
- get_file_list, 11, 18, 19, 24, 26, 28, 36, 37, 50, 62, 63, 67, 68
- get_fine_mapping, 21, 25, 35, 44, 52, 54–57, 61
- get_full_get_collapsed_gene_model_exon, 11, 18, 19, 24, 26, 28, 36, 37, 50, 62, 63, 67, 68
- get_functional_annotation, 11, 18, 19, 24, 26, 27, 36, 37, 50, 62, 63, 67, 68
- get_gene_expression, 12, 13, 15, 16, 23, 29, 39, 41–43, 59, 60, 65
- get_gene_search, 22, 29, 31, 32, 33, 45, 66
- get_genes, 22, 28, 31–33, 45, 66
- get_genomic_features, 22, 29, 31, 32, 33, 45, 66
- get_gwas_catalog_by_location, 22, 29, 31, 32, 33, 45, 66
- get_image, 34
- get_independent_eqtl, 21, 25, 34, 44, 52, 54–57, 61
- get_linkage_disequilibrium_by_variant_data, 11, 18, 19, 24, 26, 28, 36, 37, 50, 62, 63, 67, 68
- get_linkage_disequilibrium_data, 11, 18, 19, 24, 26, 28, 36, 37, 50, 62, 63, 67, 68
- get_maintenance_message, 38, 46
- get_median_exon_expression, 12, 13, 15, 16, 23, 30, 39, 41–43, 59, 60, 65
- get_median_gene_expression, 12, 13, 15, 16, 23, 30, 39, 40, 42, 43, 59, 60, 65
- get_median_junction_expression, 12, 13, 15, 16, 23, 30, 39, 41, 41, 43, 59, 60, 65
- get_median_transcript_expression, 12, 13, 15, 16, 23, 30, 39, 41, 42, 42, 59, 60, 65
- get_multi_tissue_eqtls, 21, 25, 35, 43, 52, 54–57, 61
- get_neighbor_gene, 22, 29, 31–33, 45, 66
- get_news_item, 38, 46
- get_sample_biobank_data, 10, 46
- get_sample_datasets_endpoints, 11, 18, 19, 24, 26, 28, 36, 37, 48, 62, 63, 67, 68
- get_service_info, 51
- get_significant_single_tissue_eqtls, 21, 25, 35, 44, 51, 54–57, 61
- get_significant_single_tissue_eqtls_by_location, 21, 25, 35, 44, 52, 53, 55–57, 61
- get_significant_single_tissue_ieqtls, 21, 25, 35, 44, 52, 54, 54, 56, 57, 61
- get_significant_single_tissue_isqtls, 21, 25, 35, 44, 52, 54, 55, 55, 57, 61
- get_significant_single_tissue_sqtls, 21, 25, 35, 44, 52, 54–56, 57, 61
- get_single_nucleus_gex, 12, 13, 15, 16, 23, 30, 39, 41–43, 58, 60, 65
- get_single_nucleus_gex_summary, 12, 13, 15, 16, 23, 30, 39, 41–43, 59, 59, 65
- get_sqtl_genes, 21, 25, 35, 44, 52, 54–57, 60

`get_subject`, [11](#), [18](#), [19](#), [24](#), [26](#), [28](#), [36](#), [37](#),
[50](#), [62](#), [63](#), [67](#), [68](#)
`get_tissue_site_detail`, [11](#), [18](#), [19](#), [24](#), [26](#),
[28](#), [36](#), [37](#), [50](#), [62](#), [63](#), [67](#), [68](#)
`get_tissue_site_detail()`, [3](#), [5](#), [7–9](#), [12](#),
[13](#), [15](#), [16](#), [21](#), [23](#), [25](#), [30](#), [35](#), [39–41](#),
[43](#), [47](#), [50](#), [52](#), [53](#), [55–58](#), [60](#), [61](#), [64](#)
`get_top_expressed_genes`, [12](#), [13](#), [15](#), [16](#),
[23](#), [30](#), [39](#), [41–43](#), [59](#), [60](#), [64](#)
`get_transcripts`, [22](#), [29](#), [31–33](#), [45](#), [65](#)
`get_variant`, [11](#), [18](#), [19](#), [24](#), [26](#), [28](#), [36](#), [37](#),
[50](#), [62](#), [63](#), [66](#), [68](#)
`get_variant_by_location`, [11](#), [18](#), [19](#), [24](#),
[26](#), [28](#), [36](#), [37](#), [50](#), [62](#), [63](#), [67](#), [67](#)